



\*\*\*spare part\*\*\* SIMATIC S7-300, front connector with screw connections, 40-pole

General information	
Product type designation	Front connector
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Accessories	
belongs to product	S7-300
Connection method	
Connection I/O signals	
• Connection method	Screw terminals
• Number of lines per connection	1; Or 2 cables up to 0.75 mm <sup>2</sup> (total) in a shared end sleeve
Conductor cross-section in mm <sup>2</sup>	
— Connectable cable cross-sections for massive cables, min.	0.14 mm <sup>2</sup>
— Connectable cable cross-sections for massive cables, min.	0.75 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.14 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, max.	0.75 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.14 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, max.	0.75 mm <sup>2</sup>
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	19
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	19
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	19
Wire end processing	

— Stripped length of cables, min.	6 mm
— Stripped length of cables, max.	6 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Design A, 5 mm to 7 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Design E, up to 6 mm long

#### Mounting

— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
— Tightening torque, min.	0.4 N·m
— Tightening torque, max.	0.7 N·m

#### Dimensions

Width	21.6 mm
Height	125 mm
Depth	40.9 mm

#### Weights

Weight, approx.	137 g
-----------------	-------

#### Classifications

	Version	Classification
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

#### Approvals / Certificates

##### General Product Approval



EG-Konf.

[China RoHS](#)

[Manufacturer Declaration](#)

[Miscellaneous](#)



RCM

##### General Product Approval

EMV

For use in hazardous locations



EG-Konf.



RCM



ATEX

[EM](#)

##### For use in hazardous locations

##### Maritime application



IECEX

[Miscellaneous](#)



ATEX

[CCC-Ex](#)



ABS

[NK / Nippon Kaiji Kyokai](#)

##### Maritime application



---

last modified:

4/7/2025 