

Eaton FWP-6A14F

Catalog Number: FWP-6A14F

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 700 Vdc (UL), 690 Vac (IEC), 6A, 200 kAIC at 700 Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

Product specifications

Interrupt rating

200 kAIC

Amperage Rating

6 A

Fuse type

FWP-A14F

Fuse size

14 x 51 mm

Fuse indicator

Non Indicating

Clearing (I2T)

11

Connection

Ferrule end x ferrule end

Material

Ceramic

Watt losses

Release characteristic

Other

Frequency rating - max

62 Hz

Accessories

CH14 Modular
fuse holder
FW14-PCB

Voltage rating

700 V

Construction size

14 mm x 51 mm

Color

White

Quantity

10

Utilization category

aR (accompanied semiconductor
protection)

Type



2 W

High speed fuse

[Fuse shape](#)

[Used with](#)

Finger safe holders/blocks and striker

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

[CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

Breaking capacity

200 kA

Class

Class aR

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Frequency rating - min

45 Hz

Pre arc (I2T)

2

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia