

Product datasheet

Specifications



Acti9 - ITA - 4C yearly time switch - 24 hours + 7 days + year

CCT15940

Main

range of product	Acti9
Product name	Acti9 ITA
Device short name	ITA
Product or component type	Yearly programmable time switch
Device application	Building
Battery type	Lithium
Number of channels	4
User language	Hungarian Norwegian Spanish French Dutch Italian German English Danish Portuguese Swedish Romanian Czech Polish Finnish
Colour tint	White (RAL 9003)

Complementary

Maximum switching current	10 A - 250 V AC pf = 1 6 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V AC at 50/60 Hz
Number of inputs	2 input(s) impulse and maintained
Accuracy	+/- 0.5 s/day 20 °C
Cycle duration	24 hours + 7 days + year
Maximum number of switchings	300
Minimum interval duration	1 s
Function available	Cycle programming Manual or software programming Pulse programming External input for override Time synchronisation via antenna possible Automatic winter/summer time changeover
Display type	Backlit LCD
Battery life	10 year(s)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Backup time	10 years time and program saving
Type of setting	PIN code Absence for holidays function
Connections - terminals	screw terminals
Mounting support	DIN rail
9 mm pitches	8
Width	71.5 mm
Height	90 mm
Depth	63 mm
Function	Pulse programming
Absence for holidays	Yes
Time changeover	Automatic
Updated by	GPS DCF77
Compatibility code	ITA
Market segment	Small commercial

Environment

Ambient air temperature for operation	-30...55 °C
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	7.800 cm
Package 1 Length	12.500 cm
Package 1 Weight	381.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.025 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	5c23d91a-4c63-483e-b70a-45310671b035
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins