

Product data sheet

Specifications



RACK ATS, 20A/208V, 16A/230V, C20 IN, (8) C13 (1) C19 OUT



AP7723

⚠ Discontinued on: Jun 28, 2023

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Output voltage	230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Provided Equipment	Documentation CD Rack Mounting brackets RS-232 configuration cable Warranty card
Input Frequency	47...63 Hz
Max line current	20 A
Input current limits	20 A
Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	8 IEC 60320 C13 1 IEC 60320 C19
Protection Type	Without circuit breaker

Complementary

Color	Black
Height	1.7 in (4.4 cm)
Width	17.008 in (43.2 cm)
Depth	9.02 in (22.9 cm)
Net Weight	8.66 lb(US) (3.93 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	cUL Listed CE UL Listed
Standards	EN 55022 Class A FCC Part 15 class A
Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

GTIN	731304255857
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.5 in (11.4 cm)
Package 1 Width	23.6 in (60 cm)
Package 1 Length	13.7 in (34.9 cm)
Package weight(Lbs)	12.540 lb(US) (5.688 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	9
Package 2 Height	19.7 in (50 cm)
Package 2 Width	31.5 in (80 cm)
Package 2 Length	47.2 in (120 cm)
Package 2 Weight	134.79 lb(US) (61.14 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant By Exemption](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Circularity Profile

[End of Life Information](#)

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

