INDUSTRIAL COMPONENT DATA

DILA-XHI22 276426 Y7-276426 EATON ELECTRIC Auxiliary contact module, 2N/O+2N/C, surface mounting, screw conn..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHI22



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHI22
Catalog number	Y7-276426
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-E5BAAE341A
Generated	2026-11-23

Product Overview

Auxiliary contact module, 2N/O+2N/C, surface mounting, screw connection
DILA-XHI22
Eaton Moeller® series DILA Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILA, DILM7 - DILM38
Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Mounting type: Front fixing, For use with: DILA(C)…, DILM(C)7…, DILM(C)9…, DILM(C)12…, DILM(C)15… , DILM(C)17…, DILM(C)25…, DILM(C)32…, DILM38…, DILMP20…, DILMP32…, DILMP45…, DILL…, DILMF8…, DILMF11…, DILMF14…, DILMF17…, DILMF25…, DILMF32…, Type: Fron

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications
Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 276426 Model Code DILA-XHI22 EAN 4015082764265 UPC 782116354597 Product Length/Depth 45 mm Product Height 38 mm Product Width 36 mm Product Weight 0.049 kg Certifications IEC/EN 60947-4-1

CSA-C22.2 No. 14-05
UL Category Control No.: NKCR
CSA
UL 508
VDE 0660
CSA Class No.: 3211-03
CE
IEC/EN 60947
CSA File No.: 012528
UL
UL File No.: E29184 Features & Functions
Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions For standard applications Fitted with: Interlocked opposing contacts
Switching elements according to EN 50005 Number of poles Four-pole Electric connection type Screw connection General Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Lifespan, mechanical 10,000,000 Operations (DC operated)
10,000,000 Operations (AC operated) Model Top mounting Mounting method Front fastening Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated from fron...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHI22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.