



APEXON SOLUTIONS LLC TECHNICAL DATA SHEET: MLR25PRL45203051 DOCUMENT
STATUS: RELEASED FOR PROCUREMENT

Core Identification: Product ID (MPN): MLR25PRL45203051 Manufacturer: ICAR
Product Series: ECOFILL MLR 25 PRL Component Type: Motor Run Capacitor Country of
Origin: Italy

Electrical Specifications: Capacitance: 2 μ F Capacitance Tolerance: $\pm 5\%$ (Class J) Rated
Frequency: 50/60 Hz Dielectric Material: Metallized Polypropylene Film Safety Class: S0

Voltage and Service Life Classifications: Rated Voltage (Class A): 400V AC (30,000
hours) Rated Voltage (Class B): 450V AC (10,000 hours) Rated Voltage (Class D): 500V
AC (1,000 hours)

Physical Dimensions and Construction: Diameter: 30 mm Length: 51 mm Connection
Type: 6.3 mm Faston Terminals Mounting: Detachable Bottom Stud (M8) Housing
Material: Plastic (Resin Filled) Construction: Self-healing metallized film

Environmental and Compliance: Climatic Category: 40/085/21 Standards & Approvals:
EN 60252-1, VDE Primary Applications: Single-phase asynchronous motors, pumps,
compressors, HVAC

APEXON SOLUTIONS LLC DISCLAIMER: The technical data provided herein is for
informational purposes only. While Apexon Solutions LLC strives for accuracy, we
assume no liability for errors, omissions, or the suitability of this component for specific
end-user applications. Procurement teams must verify all critical tolerances with the
manufacturer's primary engineering documentation prior to purchase.

Apexon Solutions LLC | jun@apexonsupply.com | 111 W 2nd St, Unit #536 Casper, WY
82601