



表 1

序号	熔断体型号				外形尺寸 / 尺码 (mm)	额定电压 (V)	额定电流 (A)	重量 (g)
	本公司		国内外同类产品					
	普通 (gG)	快速 (aR)	普通 (gG)	快速 (aR)	图号 $\phi D \times L$			
0101	RO06	RS06	-	-	1.1 $\phi 12.7 \times 29$	250/380	1~32	6.5
0102	RO07	RS07	-	-	1.1 $\phi 30 \times 57$	600	10~100	75
0103	RO09	RS09	-	-	1.1 $\phi 18 \times 37$	500	2~63	17.4
0104	RO10	RS10	-	-	1.1 $\phi 18 \times 50$	500	2~63	23.5
0105	RO11	RS11	AJT JKS LPJ	ACL	1.1 $\phi 21 \times 58$	600	2~32	51.5
0106	RO12	RS12	AJT JKS LPJ	ACL	1.1 $\phi 27 \times 60$	600	35~100	90
0107	RO13	RS13	-	-	1.1 $\phi 15 \times 50$	500	2~40	23.2
0108	RO14	RS14	RT19-16 gF1	-	1.1 $\phi 8.5 \times 31.5$	500	0.5~25	4.4
0109	RO14A	RS14A	-	-	1.1 $\phi 8.5 \times 23$	250	0.5~20	3.5
0110	RO14B	RS14B	-	-	1.1 $\phi 8.5 \times 36$	380/500	0.5~20	5.0
0111	RO15	RS15	RT14-20 gF2 RT18-32 RT19-25	KTK KLM	1.1 $\phi 10.3 \times 38$	500/690	0.5~32	7.7
0112	RO15A	RS15A	-	-	1.1 $\phi 10.3 \times 25.8$	250	0.5~16	4.8
0113	RO15B	RS15B	-	-	1.1 $\phi 10.3 \times 31.5$	250/500	0.5~25	5.8
0114	RO15C	RS15C	-	-	1.1 $\phi 10.3 \times 34$	380/500	0.5~32	6.2
0115	RO15D	RS15D	-	-	1.1 $\phi 10.3 \times 57$	600	2~32	11
0116	RO16	RS16	RT14-32 gF3 RT18-63 RT19-40	FWP	1.1 $\phi 14.3 \times 51$	500/690	2~63	20.5
0117	RO16A	RS16A	-	-	1.1 $\phi 14.3 \times 38$	500	2~50	15.6
0118	RO16B	RS16B	-	-	1.1 $\phi 14.3 \times 45$	500	2~50	18.5
0119	RO16C	RS16C	-	-	1.1 $\phi 14.3 \times 67$	500	2~50	27.5
0120	RO17	RS17	RT14-63 gF4 RT18-125 RT19-100	URE2263	1.1 $\phi 22.2 \times 58$	500/690	10~125	58
0121	RO18	RS18	-	-	1.1 $\phi 9.6 \times 30$	380	0.5~25	4.8
0122	RO19	RS19	-	-	1.1 $\phi 20.5 \times 127$	600	0.5~32	91.2
0123	RO19A	RS19A	-	-	1.1 $\phi 20.5 \times 76$	250/500	0.5~63	63
0124	RO19B	RS19B	-	-	1.1 $\phi 20.5 \times 114$	600	0.5~32	85
0125	RO19C	RS19C	-	-	1.1 $\phi 27 \times 139$	600	32~63	172.4
0126	RO19D	RS19D	-	-	1.1 $\phi 27 \times 147$	600	32~63	160
0127	RO54	RS54	-	-	1.1 $\phi 5 \times 20$	250	0.5~16	1
0128	RO55	RS55	-	-	1.1 $\phi 5 \times 25$	250	0.5~16	1.3
0129	RO56	RS56	-	-	1.1 $\phi 6 \times 20$	250	0.5~16	1.7
0130	RO57	RS57	-	-	1.1 $\phi 6.3 \times 25$	250	0.5~16	2.1
0131	RO58	RS58	-	-	1.1 $\phi 6.3 \times 31.5$	250/500	0.5~16	2.5
0132	8SY5015	8SY5015	-	-	1.1 $\phi 11 \times 77$	1140	2	23
0133	8SY5016	8SY5016	-	-	1.1 $\phi 11 \times 77$	1140	4	23
0134	8SY5017	8SY5017	-	-	1.1 $\phi 11 \times 77$	1140	6	23
0135	8SY5018	8SY5018	-	-	1.1 $\phi 11 \times 77$	1140	8	23
0136	8SY5019	8SY5019	-	-	1.1 $\phi 11 \times 77$	1140	10	23

图 1.1

APEXON SOLUTIONS DISCLAIMER: The technical data provided herein is for informational purposes only. While Apexon Solutions LLC strives for accuracy, we assume no liability for errors, omissions, or the suitability of this component for specific applications. All specification