



APEXON SOLUTIONS LLC TECHNICAL DATA SHEET DOCUMENT ID: TDS-MIRO-RO15

Product Identification: Manufacturer: MIRO Part Number: RO15 Series: RT18-32

Component Type: Cylindrical Fuse Link

Electrical Specifications: Rated Current: 16 A Rated Voltage: 500V / 690V AC Utilization

Category: aM (Partial-range motor protection) Breaking Capacity: 100 kA System

Compatibility: AC Systems

Mechanical and Construction: Fuse Size: 10 x 38 mm Body Material: High-grade

Ceramic Contact Material: Silver-plated Copper Form Factor: Cylindrical

Application Suitability: Primary Use: Motor protection Secondary Use: Industrial control

circuits Load Compatibility: Inductive loads Protection Type: Short-circuit protection

表 1

| 序号 | 熔断体型号 | | 国内外同类产品 | | 外形尺寸 / 尺码 (mm) | | 额定电压 (V) | 额定电流 (A) |
|------|-------|-------|----------------------------------|---------|----------------|-------------------------|----------|----------|
| | 本公司 | | 普通 (gG) | 快速 (aR) | 图号 | $\phi D \times L$ | | |
| 0101 | RO06 | RS06 | - | - | 1.1 | $\phi 12.7 \times 29$ | 250/380 | 1~32 |
| 0102 | RO07 | RS07 | - | - | 1.1 | $\phi 30 \times 57$ | 600 | 10~100 |
| 0103 | RO09 | RS09 | - | - | 1.1 | $\phi 18 \times 37$ | 500 | 2~63 |
| 0104 | RO10 | RS10 | - | - | 1.1 | $\phi 18 \times 50$ | 500 | 2~63 |
| 0105 | RO11 | RS11 | AJT JKS LPJ | ACL | 1.1 | $\phi 21 \times 58$ | 600 | 2~32 |
| 0106 | RO12 | RS12 | AJT JKS LPJ | ACL | 1.1 | $\phi 27 \times 60$ | 600 | 35~100 |
| 0107 | RO13 | RS13 | - | - | 1.1 | $\phi 15 \times 50$ | 500 | 2~40 |
| 0108 | RO14 | RS14 | RT19-16 gF1 | - | 1.1 | $\phi 8.5 \times 31.5$ | 500 | 0.5~25 |
| 0109 | RO14A | RS14A | - | - | 1.1 | $\phi 8.5 \times 23$ | 250 | 0.5~20 |
| 0110 | RO14B | RS14B | - | - | 1.1 | $\phi 8.5 \times 36$ | 380/500 | 0.5~20 |
| 0111 | RO15 | RS15 | RT14-20 gF2 RT18-32 RT19-25 | KTK KLM | 1.1 | $\phi 10.3 \times 38$ | 500/690 | 0.5~32 |
| 0112 | RO15A | RS15A | - | - | 1.1 | $\phi 10.3 \times 25.8$ | 250 | 0.5~16 |
| 0113 | RO15B | RS15B | - | - | 1.1 | $\phi 10.3 \times 31.5$ | 250/500 | 0.5~25 |
| 0114 | RO15C | RS15C | - | - | 1.1 | $\phi 10.3 \times 34$ | 380/500 | 0.5~32 |
| 0115 | RO15D | RS15D | - | - | 1.1 | $\phi 10.3 \times 57$ | 600 | 2~32 |
| 0116 | RO16 | RS16 | RT14-32 gF3 RT18-63 RT19-40 | FWP | 1.1 | $\phi 14.3 \times 51$ | 500/690 | 2~63 |
| 0117 | RO16A | RS16A | - | - | 1.1 | $\phi 14.3 \times 38$ | 500 | 2~50 |
| 0118 | RO16B | RS16B | - | - | 1.1 | $\phi 14.3 \times 45$ | 500 | 2~50 |
| 0119 | RO16C | RS16C | - | - | 1.1 | $\phi 14.3 \times 67$ | 500 | 2~50 |
| 0120 | RO17 | RS17 | RT14-63 gF4 RT18-125 RT19-100 | URE2263 | 1.1 | $\phi 22.2 \times 58$ | 500/690 | 10~125 |

APEXON SOLUTIONS DISCLAIMER: The technical data provided herein is for informational purposes only. While Apexon Solutions LLC strives for accuracy, we assume no liability for errors, omissions, or the suitability of this component for specific applications. All specifications are subject to manufacturer revisions. Procurement teams must verify all critical parameters with the manufacturer's official datasheet prior to integration.