



APEXON SOLUTIONS LLC TECHNICAL DATA SHEET DOCUMENT ID: TDS-MIRO-RO15

Product Identification: Manufacturer: MIRO Part Number: RO15 Series: RT18-32

Component Type: Cylindrical Fuse Link

Electrical Specifications: Rated Current: 2 A Rated Voltage: 500V / 690V AC Utilization

Category: aM (Partial-range motor protection) Breaking Capacity: 100 kA System

Compatibility: AC Systems

Mechanical and Construction: Fuse Size: 10 x 38 mm Body Material: High-grade

Ceramic Contact Material: Silver-plated Copper Form Factor: Cylindrical

Application Suitability: Primary Use: Motor protection Secondary Use: Industrial control

circuits Load Compatibility: Inductive loads Protection Type: Short-circuit protection

表 1

序号	熔断体型号		国内外同类产品		外形尺寸 / 尺码 (mm)		额定电压 (V)	额定电流 (A)
	本公司		普通 (gG)	快速 (aR)	图号	φD × L		
0101	RO06	RS06	-	-	1.1	φ12.7 × 29	250/380	1~32
0102	RO07	RS07	-	-	1.1	φ30 × 57	600	10~100
0103	RO09	RS09	-	-	1.1	φ18 × 37	500	2~63
0104	RO10	RS10	-	-	1.1	φ18 × 50	500	2~63
0105	RO11	RS11	AJT JKS LPJ	ACL	1.1	φ21 × 58	600	2~32
0106	RO12	RS12	AJT JKS LPJ	ACL	1.1	φ27 × 60	600	35~100
0107	RO13	RS13	-	-	1.1	φ15 × 50	500	2~40
0108	RO14	RS14	RT19-16 gF1	-	1.1	φ8.5 × 31.5	500	0.5~25
0109	RO14A	RS14A	-	-	1.1	φ8.5 × 23	250	0.5~20
0110	RO14B	RS14B	-	-	1.1	φ8.5 × 36	380/500	0.5~20
0111	RO15	RS15	RT14-20 gF2 RT18-32 RT19-25	KTK KLM	1.1	φ10.3 × 38	500/690	0.5~32
0112	RO15A	RS15A	-	-	1.1	φ10.3 × 25.8	250	0.5~16
0113	RO15B	RS15B	-	-	1.1	φ10.3 × 31.5	250/500	0.5~25
0114	RO15C	RS15C	-	-	1.1	φ10.3 × 34	380/500	0.5~32
0115	RO15D	RS15D	-	-	1.1	φ10.3 × 57	600	2~32
0116	RO16	RS16	RT14-32 gF3 RT18-63 RT19-40	FWP	1.1	φ14.3 × 51	500/690	2~63
0117	RO16A	RS16A	-	-	1.1	φ14.3 × 38	500	2~50
0118	RO16B	RS16B	-	-	1.1	φ14.3 × 45	500	2~50
0119	RO16C	RS16C	-	-	1.1	φ14.3 × 67	500	2~50
0120	RO17	RS17	RT14-63 gF4 RT18-125 RT19-100	URE2263	1.1	φ22.2 × 58	500/690	10~125

APEXON SOLUTIONS DISCLAIMER: The technical data provided herein is for informational purposes only. While Apexon Solutions LLC strives for accuracy, we assume no liability for errors, omissions, or the suitability of this component for specific applications. All specifications are subject to manufacturer revisions. Procurement teams must verify all critical parameters with the manufacturer's official datasheet prior to integration.