SIEMENS

Data sheet 3VL3725-3AA36-0AA0



circuit breaker VL250L without Electronic Trip Unit very high breaking capacity Icu=100kA/415V AC, 3-pole In=< 250A, rated current without auxiliary release with screw terminal connections for switching unit and Electronic Trip Unit

Weight	1.969 kg
Net Weight	1.969 kg

General Product Approval					Test Certificates
CCC	Confirmation	UKCA	CE EG-Konf.	EAC	Special Test Certificate

other		Environment	
Miscellaneous	Confirmation	Miscellaneous	Environmental Confirmations	Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3725-3AA36-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL3725-3AA36-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3725-3AA36-0AA0
CAx-Online-Generator
http://www.siemens.com/cax
Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation





last modified: 12/20/2020

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens