



FGB-A-3E

圆管快速熔断器

690VAC 2A-32A



产品基本资料

- 符合IEC60269;
- 额定电压: AC690V或低于;
- 额定电流: 2-32A;
- 保护类别: gG (IEC);
- 分断能力: 100kA (COSΦ>0.2);
- 额定频率: 45-62Hz (AC);
- 产品和包装符合欧盟RoHS指令;
- 安装在TSA1038系列底座, 或专用的铜卡座上;

序号	型号	尺寸代码	额定电流 A	I ² t (A ² s)		功耗 W	备注
				弧前	熔断		
1	FGB-A-3E2A	3E	2	2.1	22	0.9	配用TSA1038底座
2	FGB-A-3E3A		3	7	34	1	
3	FGB-A-3E4A		4	9	44	1.2	
4	FGB-A-3E5A		5	19	92	1.3	
5	FGB-A-3E6A		6	29	140	1.5	
6	FGB-A-3E8A		8	60	290	1.8	
7	FGB-A-3E10A		10	93	483	1.9	
8	FGB-A-3E12A		12	134	696	2.1	
9	FGB-A-3E16A		16	302	1565	2.4	
10	FGB-A-3E20A		20	537	2782	2.6	
11	FGB-A-3E25A		25	955	4946	2.8	
12	FGB-A-3E32A		32	1645	8520	3.2	

产品外形尺寸 (mm)

3E-熔断件外形及安装尺

