



APEXON SOLUTIONS LLC TECHNICAL DATA SHEET DOCUMENT ID: TDS-SINOFUSE-TSA1485-K2

Product Identification: Manufacturer: Xi'an Sinofuse Electric Co., Ltd. Part Number: TSA1485-K2 Order Code: TSA1485-K2 Component Type: 2-Pole Photovoltaic Fuse Holder

Electrical Specifications: Rated Operational Current (Ie): 40 A Rated Operational Voltage (Ue): 1500 VDC (DC-20B) Rated Insulation Voltage (Ui): 1600 V Rated Impulse Withstand Voltage (Uimp): 12 kV Rated Short-Circuit Capacity (Icc): 50 kA Number of Poles: 2-Pole (2P)

Mechanical and Physical: Compatible Fuse Size: 14 x 85 mm Degree of Protection: IP20 Flammability Rating: UL94-V0 Housing Construction: Flame-retardant polymer

Installation and Termination: Terminal Wire Range: 2.0 to 16 mm² (75°C Cu Wire Only) Tightening Torque: 2.5 to 3.5 N·m

Compliance and Standards: International Standards: IEC 60947-3, UL 4248-1 National Standard: GB/T 14048.3

Application Suitability: Primary Use: Photovoltaic overcurrent and short-circuit protection Secondary Use: Solar combiners, Distribution boxes System Compatibility: High-voltage solar utility and industrial DC power systems Safety Features: Finger-safe design, robust disconnecter

APEXON SOLUTIONS DISCLAIMER: The technical data provided herein is for informational purposes only. While Apexon Solutions LLC strives for accuracy, we assume no liability for errors, omissions, or the suitability of this component for specific applications. All specifications are subject to manufacturer revisions. Procurement teams must verify all critical parameters with the manufacturer's official datasheet prior to integration.